


CENTER BONDED RUBBER BUSH



H = Height
 D1 = Top Diameter
 D2 = Bottom Diameter
 F = Depth of Nut

<p>Features: They are simple and low cost fail-safe mounts. They are made of natural rubber compound standard but can also be supplied in CR, NBR or EPDM.</p>	<p>Applications:</p> <ul style="list-style-type: none"> • Vehicle cabs • Engines • Compressors • Pumps • Air conditioning units • Engine exhaust mounts (in high temperature rubber compound) 	<p>Material: Natural Rubber</p>
--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	-------------------------------------------------------------

Article No:	H1(mm)	H2 (mm)	D1 (mm)	D2(mm)	F (mm)	Max Axial (kg)	Max. Deflection (mm)
VCBB2818	17.5	5.6	27.7	20.1	10	56	0.64
VCBB4525	25.4	10.4	44.5	31.5	13	155	1.02
VCBB5133	35	13.5	50.8	34.3	13	211	1.52
VCBB6423	23	16	64	38	16	334	1.62
VCBB6445	44.5	15.7	63.5	41.1	16	334	1.62
VCBB9551	50.8	25.4	95	56	20	395	1.7

This information is for guidance only. Customers are recommended to contact us for further technical information on products and applications. We reserve the right to alter specifications or withdraw products without notice.