



ANTI VIBRATION DOUBLE SHEAR BUSHINGS



The two piece Mountings are an ideal product for both mobile & static applications for reducing vibration, allowing flexibility within a system and are used for reducing stresses on brackets etc. Using washers ensures a fail-safe mounting system arrangement.

- A = Thickness Of Rubber Bush.
- B = Thickness Of Rubber Washer
- C = Height Of Rubber Washer
- D = Height Of Rubber Bush
- E = Collar Thickness
- F = Inner Diameter Of Rubber Bush
- G = Outer Diameter Of Rubber Washer

Applications:

- Construction Equipment,
- Power Generation
- Military Vehicles
- Off Road & Agricultural
- Industrial Machinery & Equipment.

Material:

Natural Rubber

Article no:	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)	F (mm)	G (mm)	Q (mm)	T (max)	T (max)	R
VDSB30	12	20	10	9	12	10	33	20	9.5	9.5	1
VDSB50	20	31	19	10	20	14	47.5	31	14	13	2
VDSB65	23	40	24	15	23	17	64	39	22	19	3
VDSB90	25	58	27	22	25	24	89	57	28.6	25	3

Article No:	45 Sha.		60 Sha.	
	Max Load (Kg)	Deflection (mm)	Max Load (kg)	Static Deflection (mm)
VDSB30	40	2.0	70	2.5
VDSB50	75	3.7	125	3.5
VDSB65	115	4.0	250	4.0
VDSB90	250	7.0	440	6.0

This information is for guidance only. Customers are recommended to contact us for further technical information on products and applications. We reserve the right to alter specifications or withdraw products without notice.